TOWN OF WAYNE 6030 MOHAWK RD, CAMPBELLSPORT, WI 262 626 4818

email: waynetown@netwurx.net

Web Page: http://www.netwurx.net/~waynetown/wayntown.htm

Carl Klemme Chairman Julie A. Kriewaldt Clerk 262 629-9199

Kieth A. Kriewaldt Culvert Inspector: 262 629-9199

If you want to create a new lot, you must provide access to a public road from the lot. If you want to access a town road, contact the Culvert Inspector. If you want to access a county road, Contact Washington County Highway Department 262 335 4435. If you wish to access a state road contact:

Andrew A. Malsom
Access Management Engineer
Systems Planning
WisDOT SE Region
141 NW Barstow ST
Waukesha, WI 53187
andrew.malsom@dot.state.wi.us

If you want to build or improve a driveway that connects to a Town Road, you must contact the culvert inspector to obtain a permit. The permit fee is \$100.00 and you must post a bond in the amount of \$500.00. If you want to create a lot, you must connect to a public road. To connect to a county road or state highway, contact the county or the state. To connect to a town road, an inspection for safe access is required before approval of the land division; the fee is \$75.00 for the inspection. Contact the culvert inspector. The culvert permit application and standards for culverts in the Town are shown below:

PERMIT NUMBER:_____ TOWN OF WAYNE PERMIT TO INSTALL ACCESS DRIVEWAY TO A TOWN ROAD

The undersigned and designated applicant requests permission to construct the driveway(s) hereinafter described on town road right of way, and in consideration of being granted permission, as evidenced by the approval of the authorized representative of the Highway Commission, binds and obligates himself to construct the driveway(s) in accordance with the description contained herein and sketches, if any, attached hereto, and to abide by the general requirements and location, design and construction requirements set forth on this form.

requirements set forth on this form.			
DESCRIPTION			
Road Name	; Washington County: Town of		
Wayne: along the	side of the highway	miles	
of			

in sec	Number of
Driveways:	Type of driveways
length) and special restrictions, interse installation, including reference to atta	t of way, culvert requirements, if any, (size and ection clearances, and other details of the proposed
A 15" x 21" or 18" diameter culvert p be installed under the driveway to pro	pipe, feet in length sha vide proper drainage along the highway.
The Driveway shall be locatedline.	feet from thelor
[] Copy of construction standards given to the applicant.	s shown on the reverse side of this form has been
bond will be refunded after occupancy demonstrates installation and restorati- highway committee or its designee has appropriate and the town clerk notified to the Culvert Inspector within one year is forfeited. All driveway permits sha extended by the Culvert Inspector. Sa	mount of \$500.00 for all driveway permits. The a, final grading and seeding, and final inspection on of the town road to the satisfaction of the seen accomplished and drainage on the project is d in writing. Applications for refund must be mader of the date of the Occupancy permit or the bond ll expire six (6) months after application, unless aid driveway permits are non-transferrable and nor only as stated above. This application and terms seed to:
	Applicant
(print or type name here)	
Signed:	Applicant Date:
Address:	
	Culvert

[] Permit Fee \$150.00	Tax
Key Number:	
Driveway Bond \$500.00	
Total Received:	House Number:

The following construction standard and general requirements shall apply to any culvert placed within the right-of-way and to any paved driveway approach within the right-of-way.

- a) Culverts, where required by the town shall be twenty-four (24) feet long for residential driveways and forty (40) feet long for commercial driveways.
- b) Culverts shall be installed with apron and end walls.
- c) Only new galvanized steel meeting minimum state highway gauge will be allowed.
- d) Culverts shall be laid on a bedding of three-quarter (3/4) inch road gravel and shall be backfilled with three-quarter (3/4) inch road gravel.
- e) End treatments, if used, shall be installed at a maximum of forty-five (45) degrees to the road surface and shall not exceed the driveway grade in height.
- f) Driveway grades shall be placed in a manner to maintain a pitch of one-half (1/2) inch per foot away from the roadway to the center of the ditch flow line.
- g) No concrete surface shall be allowed within the highway right-of-way.
- h) The applicant shall be responsible to call the Diggers Hot Line and any other underground utility sufficiently prior to the commencement of excavation to permit proper marking of the area.
- i) The applicant shall restore the right-of-way to the satisfaction of the Culvert Inspector and as soon as possible in order to avoid a hazard to the traveling public and excess erosion.
- j) All work within the right-of-way shall be performed in such a manner so as not to interfere with traffic on the adjoining roadway.
- k) The entire cost of installing and maintaining the driveway access and culvert, including restoration, shall be the financial responsibility of the applicant.
- The applicant agrees to hold harmless and indemnify Town of Wayne, its officers, agents and employees against any loss or damage for any personal injury or property damage sustained by reason of the exercise of this permit.

SKETCH OR OTHER SPECIAL TERMS AND CONDITIONS:	